PRODUCT SPECIFICATIONS

631B Full Body Harness

Product Description

The 631 series harnesses are lightweight, versatile, and easy to use. A great overall choice for general construction or roofing.

Product Features

- 3 point adjustment (chest and leg straps)
- Sliding back dorsal D-ring
- Hip-positioning D-rings
- Lightweight, high strength synthetic webbing
- Two universal sizes

MATERIAL SPECIFICATIONS	
Webbing	1-3/4" polyester webbing, minimum tensile strength 6,000 lbs.
Hardware	D-rings: plated alloy steel proof loaded to 3,600 lbs.
	Min tensile strength 5,000 lbs.
	Mating Buckles: plated alloy steel, min tensile strength 4,000 lbs.
Thread	black polyester nubond

PERFORMANCE SPECIFICATIONS	
ANSI User Capacity	130 to 310 lbs
OSHA User Capacity	400 lbs

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS
Two universal sizes: S-M and M-XL

100 N 13th St. • Franklin PA • 16323
877.228.9327 • 814-437-1808
frenchcreekproduction.com

WARNING: Read, understand and follow all labels and instructions prior to use, Inspect before each use. Remove from service if there is evidence of damage or excessive wear

FrenchCreek FALL SAFETY