PRODUCT SPECIFICATIONS

AF390AKZ Kevlar Shock Absorbing Lanyard

Product Description

FrenchCreek's Arc Flash lanyards offer fall protection, and protection against electrical arc-flash and arc-blast exposure. These lanyards are made from heat & flame resistant Kevlar webbing.

Product Features

- Kevlar webbing
- Harness choke loop
- Z74 (3/4" opening) locking snaphook
- Flame resistant shock & label cover
- Additonal snaphook options available

MATERIAL SPECIFICATIONS	
Webbing	1-3/4" Kevlar webbing, minimum tensile strength 7,000 lbs.
Hardware	Z74 Snaphook: 3/4" gate opening, plated cold-formed steel
	100% proof loaded to 3,600 lbs., minimum tensile 5,000 lbs.
	100% gate loaded to 3,600 lbs.
Thread	Kevlar

PERFORMANCE SPECIFICATIONS	
ANSI User Capacity	130 to 310 lbs
OSHA User Capacity	400 lbs
Lanyard Class	6' Free Fall
Arrest Force	900 lbs

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	1910.269 & 1926.954
ASTM	F887-13

SIZES/LENGTHS
6' standard length, additional lengths available

100 N 13th St. • Franklin PA • 16323
877.228.9327 • 814-437-1808
frenchcreekproduction.com

WARNING: Read, understand and follow all labels and instructions prior to use, Inspect before each use. Remove from service if there is evidence of damage or excessive wear

FrenchCreek FALL SAFETY